

PRODUCT CATALOG




Counteract[®]
counteractbalancing.com



•How Counteract Works	3
•Wheel Advantage Dealer Rewards	4
•The Counteract App	5

BALANCING BEADS

•Counteract Balancing Beads.....	6
•Installation Methods.....	7
•Motorcycle DIY Kits	8
•Motorcycle Balancing Beads.....	9
•Ready-Balance Motorcycle Tubes	10
•ATV/UTV DIY Kits & Trailer DIY Kits.....	11
•ECO Balancing Beads	12
•ECO XL Balancing Beads	13

WHEEL MAINTENANCE TOOLS

•Wheel Pro.....	14
•Socket Pro - Commercial.....	15
•Socket Pro - Automotive	16
•Universal Sockets.....	17

MAINTENANCE ACCESSORIES

•Tire Lube And Mounting Paste.....	18
•Liquid Tire Lube.....	19
•Electric Vehicle Tire Lube	20
•5th Wheel Grease	21

WHEEL ACCESSORIES

•Wheel Totes & Felt Covers	22
•Tire Mark-All Crayons	23
•Wheel Centering Sleeves.....	24
•Tire Valves	25
•Valve Accessories.....	26
•Other Wheel Accessories.....	27
•Zafety Lug Lock®	30
•Wheel Weights	32


APPLICATION CHARTS

•Light/Medium/Heavy Truck	34
•All Terrain & Mud Terrain.....	36
•Motorcycle	37
•ATV/UTV.....	38
•Vintage & Classic Cars.....	39
•Trailer	40
•RV/Bus	41

MARKETING

•Marketing Materials	42
•QR Link/Follow Us On Social Media	43

The balancing beads are distributed around the tire as it begins to roll, through centrifugal force. As the centrifugal force increases, the heavy spot pulls up and down on the suspension, making the beads move in the opposite direction of the downward and upward motion, through inertia. The beads continue to migrate until the complete wheel assembly is balanced.



BENEFITS



IMPROVE FUEL ECONOMY

Counteract is the only balancing product in the world proven to increase fuel economy. Counteract has demonstrated savings of at least 2.2% in two separate SAE J1321 and TMC RP-1102 Type II Fuel Tests. Don't believe us? You can download and review the tests yourself at www.cbbtests.com



REDUCE VIBRATION

There is more to balance than just the tire and wheel. Counteract's unique technology will also balance everything rotating on the axle end including the brake drum and hub, while readjusting itself on the go when experiencing new and changing out of balance conditions. Something wheel weights cannot do.



REDUCE MAINTENANCE COSTS

Heavy vibration for extended periods of time is one of the leading causes of maintenance issues. On average it takes 10-12 minutes to balance a transport truck tire with wheel weights. Using Counteract, it only takes the time needed to mount the tire.



INCREASE TIRE LIFE

Counteract Balancing Beads reduces rolling resistance of the tire up to 18%. This, in turn, reduces tire wear. When a tire and complete wheel assembly is properly balanced, on average, Counteract is known to increase tire life by at least 30%.



ENVIRONMENTALLY FRIENDLY

Counteract is manufactured from recycled tempered glass, utilizing minimal new raw materials. The beads are 99.9% glass with a special coating that allows them to repel and resist moisture. Lead weights commonly fall off the rim while driving, damaging the surrounding environment, where counteract remains inside for the life of the tire.

LEARN HOW IT WORKS



SEE IT IN ACTION



WHEEL ADVANTAGE DEALER REWARDS

Unlock A World Of Rewards With Wheel Advantage

Our innovative program offers you the chance to earn valuable reward points that seamlessly translate into a treasure trove of Counteract Merchandise.

What's In Store?

Points on Points

Collect QR Code vouchers found in full cases of Counteract Balancing Beads*, scan and trade them for some fabulous rewards.

Simplicity At Its Best

Our new app makes redeeming rewards as easy as a tap.

First Dibs

Get exclusive access to deals and offers crafted just for our dealer fam.



Case of Beads (3oz to 20oz)
REDEMPTION VALUE
10,000 Points



Mounting Lube - 4x8lb
REDEMPTION VALUE
8,000 Points



Centering Sleeves - 100pk
REDEMPTION VALUE
7,000 Points



Injection Pump
REDEMPTION VALUE
7,000 Points



Air Driver
REDEMPTION VALUE
6,000 Points

Accelerate Your Points Collection

QR Code Vouchers are available in Counteract cases*, zoom straight to rewards via the app – no stamps needed! Remember, each QR code can only be redeemed once, and keep an eye out for exclusive opportunities during special promotions and events.

*Please note that participation in the Wheel Advantage Dealer Rewards Program is at the discretion of individual distributors. As such, not all distributors may choose to participate in the program. Consequently, Counteract products distributed through non-participating distributors will not include the Wheel Advantage Reward QR Code Vouchers.



Still Have Balancing Bucks?

Your Counteract Balancing Bucks (old-style coupons) are still worth their weight in rewards. Mail them in to convert them to Wheel Advantage Points. Full case coupon? That's 1000 points. Half case? You've got 500 points coming your way.

Include your email when mailing coupons for a seamless account update.

Counteract[®] Balancing Beads App

Download the Counteract Balancing Beads App for quick Counteract calculations for any vehicle. Plus, access the Wheel Advantage Dealer Rewards Program, rewarding dealers with redeemable points for Counteract merchandise.



Joining the Wheel Advantage Dealer Rewards Program is as simple as the concept itself.

1


First, download the Counteract Balancing Beads App.

2


Upon your initial login, you'll be prompted to create an account, setting the wheels in motion for your rewarding journey.

3

Follow the streamlined steps to verify your account, and you're ready to roll.



Scan the QR code to
download on your
Android or Apple device.



For a list of all rewards and more details,
download the Counteract Balancing app or visit
counteractbalancing.com/rewards

BALANCING BEADS

Refer to our Counteract Balancing Beads Application Chart on [Page 34](#)

1



2



3



4



5



6



8



10



12



14



16



20

Part #	Flow-Through Cap	CBB Cap	CBB Core	Case Quantity*	App [†]
1 oz.B		✓	✓	40	4
2 oz.B		✓	✓	32	4
3 oz.B		✓	✓	24	4
4 oz.B		✓	✓	92	1
5 oz.B		✓	✓	76	1
6 oz.B		✓	✓	64	1
8 oz.B	✓	✓	✓	52	1
10 oz.B	✓	✓	✓	40	1
12 oz.B	✓	✓	✓	36	1
14 oz.B	✓	✓	✓	32	1
16 oz.B	✓	✓	✓	28	1
20 oz.B	✓	✓	✓	24	1

Valve caps and valve cores found in each bag of Counteract Balancing Beads.

*Number of master bags per case.

†Number of balance applications per master bag.



Valve Cores



Valve Caps




Flow-Through Caps

Depending on your application, Counteract can be installed 3 different ways.



Throw In Bag

Counteract applications of 4oz and up can conveniently be thrown inside the tire during the mounting process. Simply open the branded Counteract bag and remove the clear bag containing the beads and place it in the tire cavity. Once the wheel begins to roll, the bag will break on its own and allow the beads to disperse inside the tire. For applications 3oz and under we recommend pouring the beads into the tire, installing through the valve stem if there is no TPMS or tear the bag before placing it inside the tire.



Injection Pump

The Injection Pump Method is suited for any size application. It requires the Counteract Injection Pump, part# CBB-IP and an airline. This is the quickest method and doesn't require the tire to be dismounted.



Injection Bottle

1. Cut the Counteract bottle spout above the indicated mark. Remove the bottle cap and carefully pour the beads into the injection bottle. Attach clear tube to the bottle cap spout.
2. Rotate the wheel so the valve stem is at the bottom, deflate the tire by removing the valve core and then place one end of the clear tube over the valve stem.
3. Invert the Counteract bottle and squeeze repeatedly to get all the Counteract Balancing Beads to flow down the clear tube into your tire.
4. Use the airline to clear the valve stem then screw the Counteract valve core into the valve stem. Re-inflate the tire to the manufacturers' recommended pressure and screw the supplied valve cap on.

For details visit www.counteractbalancing.com/installation

BALANCING BEADS

Refer to our Motorcycle Application Chart on [Page 37](#)

KIT A



KIT B



KIT C



KIT D



KIT E



KIT F



KIT G

Each Motorcycle DIY Kit Contains:



Valve Cores



Injection Tube



Valve Caps



Valve Core Tool

Clear Bags
(with either 1oz, 2oz or 3oz of beads)Injection Bottle
(with either 1oz, 2oz or 3oz of beads inside)

Part #	App*	Injection Bottle	Core Tool	Cap & Core	Kits per Case
KIT A	2x1oz	✓	✓	✓	40
KIT B	1x1oz, 1x2oz	✓	✓	✓	40
KIT C	1x1oz, 1x3oz	✓	✓	✓	40
KIT D	2x2oz	✓	✓	✓	40
KIT E	1x2oz, 1x3oz	✓	✓	✓	40
KIT F	1x2oz, 2x3oz	✓	✓	✓	40
KIT G	2x2oz, 1x3oz	✓	✓	✓	40

*Number of balance applications per kit

Motorcycle Dealer Bags



MK1oz



MK2oz



MK3oz



Motorcycle Service Packs



MKSP1



MKSP2



MKSP3



Part #	App*	Cores	Caps	Case Quantity
MK1oz	4x1oz	✓	✓	40
MK2oz	4x2oz	✓	✓	32
MK3oz	4x3oz	✓	✓	24
MKSP1	20x1oz	✓	✓	4
MKSP2	20x2oz	✓	✓	4
MKSP3	20x3oz	✓	✓	4

*Number of balance applications per Master Pack



Got a tube type tire?
Check out Counteract's
Pre-Balanced Tubes on
Page 10

BALANCING BEADS

Rim Diameter	MFG Part NO.	Metric Size	Tire Size Fitment	Valve
10"	MKT-16	2.50/2.75-10	2.50-10, 2.75-10	TR87
	MKT-15	3.00/3.50-10	3.00-10, 3.25-10, 3.50-10, 80/90-10	TR87
12"	MKT-14	2.50/2.75-12	2.50-12, 2.75-12, 80/100-12, 100/80-12	TR6
	MKT-13	3.00/3.50-12	3.00-12, 3.25-12, 80/100-12, 100/80-12	TR6
15"	MKT-12	170/80-15	170/80-15	PV-78 (90 Degree)
16"	MKT-01	5.00/5.10-16	5.00-16, 5.10-16, 130/90-16, 140/80-16, 140/90-16, 150/80-16 MT90-16 MU90-16, MV85-16	TR6
	MKT-02	5.00/5.10-16 (90)	5.00-16, 5.10-16, 130/90-16, 140/80-16, 140/90-16, 150/80-16, MT90-16, MU90-16, MV85-16	TR87 (90 Degree)
	MKT-17	5.00/5.10-16 Side Valve	5.00-16, 5.10-16, 130/90-16, 140/80-16, 140/90-16, 150/80-16, MT90-16, MU90-16, MV85-16	TR6 Side Valve
17"	MKT-11	2.50/3.00-17	2.50-17, 2.75-17, 3.00-17, 3.10-17, 70/100-17, 80/90-17, 100/80-17	TR6
	MKT-04	4.00/4.50-17	4.00-17, 4.25-17, 4.50-17, 4.60-17, 110/90-17, 110/100-17, 120/80-17, 120/90-17, 130/80-17, 130/70-17	TR6
	MKT-03	6.00/6.50-17	150/160/170-17, 150/70-17, 170/60-17	TR6
18"	MKT-05	4.00/4.60-18	4.00-18, 4.25-18, 4.50-18, 4.60-18, 4.70-18, 110/90-18, 110/100-18, 120/80-18, 120/90-18, 130/70-18, 130/80-18, MP85-18, MR90-18	TR6
	MKT-06	5.00/5.10-18	5.00-18, 5.10-18, MT90-18, 120/100-18, 130/90-18, 140/80-18, 140/90-18, 140/70-18	TR6
	MKT-10	5.00/5.10-18 RIM LOCK	5.00-18, 5.10-18, MT90-18, 120/100-18, 130/90-18, 140/80-18, 140/90-18, 140/70-18	TR6
19"	MKT-07	3.50/4.00-19	3.50-19, 4.00-19, 4.10-19, 4.25-19, 4.60-19, 100/90-19, 110/80-19, 110/90-19, 120/80-19, MM90-19, MN90-19	TR6
21"	MKT-08	2.75/3.00-21	2.75-21, 3.00-21, 80/90-21, 80/100-21, 90/80-21, 90/90-21, 100/80-21, MJ90-21, MH90-21	TR6
23"	MKT-09	2.75/3.00-23	2.75-23, 3.00-23, 80/90-23, 80/100-23, 90/80-23, 90/90-23, 100/80-23, MJ90-23, MH90-23	TR6



The first all-in-one tire & complete wheel assembly balancing inner tube for motorcycles. Counteract's inner tubes come pre-loaded with Counteract Balancing Beads!

No wheel weights, no hassle, just ride.

BALANCING BEADS

ATV/UTV DIY Kits



Injection Bottle



Injection Tube



Valve Tool



Valve Caps



Valve Cores



ATV/UTV Kits

Scan to learn more, view the ATV/UTV application chart or watch the installation video.

Part #	App*	Injection Bottle	Core Tool	Cap & Core	Kits per Case
KIT K	4x4oz	✓	✓	✓	14
KIT L	4x6oz	✓	✓	✓	14
KIT M	4x8oz	✓	✓	✓	14
KIT N	4x10oz	✓	✓	✓	14

Trailer DIY Kits



Injection Bottle



Injection Tube



Core Tool



Valve Caps



Valve Cores



Trailer DIY Kits

Scan to learn more, view the trailer application chart or watch the installation video.

Part #	App*	Injection Bottle	Core Tool	Cap & Core	Kits per Case
DIYTK3-2PK	2x3oz	✓	✓	✓	14
DIYTK3-4PK	4x3oz	✓	✓	✓	14
DIYTK4-2PK	2x4oz	✓	✓	✓	14
DIYTK4-4PK	4x4oz	✓	✓	✓	14
DIYTK6-2PK	2x6oz	✓	✓	✓	14
DIYTK6-4PK	4x6oz	✓	✓	✓	14
DIYTK8-2PK	2x8oz	✓	✓	✓	14
DIYTK8-4PK	4x8oz	✓	✓	✓	14

*Number of balance applications per kit

BALANCING BEADS

An economical glass balancing bead from the makers of Counteract Balancing Beads

ECO Balance optimizes vehicle performance and longevity by balancing the complete rotating axle end assembly. Compatible with TPMS systems, it offers a lifetime tire balance guarantee, ensuring consistent performance. Crafted from high-quality materials, it guarantees durability and reliability.



Improves Fuel Economy



Increases Tire Life



Reduces Vehicle Vibrations

Part #	Flow-Through Cap	ECO Cap	ECO Core	Case Quantity*	App†
03-EB		✓	✓	24	4
04-EB		✓	✓	92	1
06-EB		✓	✓	64	1
08-EB	✓	✓	✓	52	1
10-EB	✓	✓	✓	40	1
12-EB	✓	✓	✓	36	1
14-EB	✓	✓	✓	32	1
16-EB	✓	✓	✓	28	1
18-EBB	✗	✗	✗	Bucket of loose ECO Beads 18 lbs with a 2oz scoop	

*Number of master bags per case.

†Number of balance applications per master bag.

Can be injected through valve stem

Check out the Injection Pump for Counteract and ECO Balancing Beads on **Page 29**



Extra large 2.5mm balancing beads

ECO Balance XL optimizes vehicle performance and longevity by balancing the complete rotating axle end assembly. Extra large 2.5mm tempered glass bead. Compatible with TPMS systems, it offers a lifetime tire balance guarantee, ensuring consistent performance. Crafted from high-quality materials, it guarantees durability and reliability. No need for a special valve core.



Improves Fuel Economy



Increases Tire Life



Reduces Vehicle Vibrations

Part #	ECO Valve Caps	Case Quantity*	App†
03-ECOXL	✓	24	4
04-ECOXL	✓	92	1
06-ECOXL	✓	64	1
08-ECOXL	✓	52	1
10-ECOXL	✓	40	1
12-ECOXL	✓	36	1
14-ECOXL	✓	32	1
16-ECOXL	✓	28	1
20-ECOXL	✓	24	1
18-EBBXL	✗	Bucket of loose ECO XL Beads 18 lbs with a 2oz scoop	

*Number of master bags per case.

†Number of balance applications per master bag.

Can NOT be injected through valve stem

WHEEL MAINTENANCE TOOLS



WHEEL PRO

Commercial Stud & Hub Cleaner



EASY SNAP-TECH DESIGN

This non-impact tool design allows for controlled cleaning without the hammering effect of an impact, which can deteriorate the tool, brushes, and application, as seen in competing products.

Unlike competing products, Counteract's Wheel Pro & Wheel Pro XL employ our Snap-Tech design with interchangeable heads for specific tasks, allowing for super quick and efficient brush changing. The vented tool body allows rust and debris to dissipate while cleaning, avoiding tool lock which can break or snap the tool body.



Wheel Pro XL



WPXL-T22

WPXL-SB22

WPXL-HB22



Wheel Pro



WP-T12

WP-SB12

WP-SB14

WP-HB1640

WP-HB1650


Part #	Product Description
WHEEL PRO XL - COVERS OVER 90% OF ALL COMMERCIAL TRUCK WHEEL-END APPLICATIONS	
WPXL-T22	Wheel Pro XL Tool (includes 22mm stud cleaning brush WPXL-SB22)
WPXL-SB22	22mm Stud Cleaning Brush Replacements - 6 pack (compatible with WPXL-SB22)
WPXL-HB22	60mm Hub Brush Replacements - 6 pack (compatible with WPXL-SB22)
WHEEL PRO - COVERS A LARGE MAJORITY OF AUTOMOTIVE/LIGHT TRUCK AND TRAILER APPLICATIONS	
WP-T12	Wheel Pro Tool (includes 12mm stud cleaning brush WP-SB12)
WP-SB12	12mm Stud Cleaning Brush Replacements - 6 pack (compatible with WP-T12)
WP-SB14	14mm Stud Cleaning Brush Replacements - 6 pack (compatible with WP-T12)
WP-HB1640	40mm Hub Brush Replacements - 6 pack (compatible with WP-T12)
WP-HB1650	50mm Hub Brush Replacements - 6 pack (compatible with WP-T12)



Socket Pro

Commercial Deep Impact Sockets

COMPATIBLE ON AT LEAST 6 DIFFERENT FASTENER TYPES:



Deep impact sockets work in cases of corroded and rounded lug-heads for commercial wheel and fastener applications.

Manufactured with quality chrome molybdenum alloy steel for superior torque and durability.



CBBS1-33



CBBS34-33



CBBS1-S5



CBBS1-S10



CBBS34-S10

Part #	Product Description		
	COMMERCIAL DEEP IMPACT SOCKETS	1" DRIVE	3/4" DRIVE
CBBS1-33	1 Piece - 1" Drive - 33mm	✓	
CBBS1-S5	5 Piece Set - 1" Drive - 17mm, 27mm, 30mm, 33mm, 35mm	✓	
CBBS1-S10	10 Piece Set - 1" Drive - 13/16", 1-1/16", 1-1/8", 1-1/4", 1-1/2", 17mm, 21mm, 33mm, 35mm, 41mm	✓	
CBBS34-33	1 Piece - 3/4" Drive - 33mm		✓
CBBS34-S10	10 Piece Set - 3/4" Drive - 13/16", 1-1/16", 1-1/8", 1-1/4", 1-1/2", 17mm, 21mm, 33mm, 35mm, 41mm		✓


WHEEL MAINTENANCE TOOLS

Socket Pro

Automotive/Light
Truck/Trailer Thin
Wall Impact Sockets

For heavy
duty jobs 

COMPATIBLE ON AT LEAST 6 DIFFERENT FASTENER TYPES:



Impact rated sockets work in cases of corrosion, rounded
lug heads, thin walls for specialty aluminum wheels, etc.

Manufactured using quality chrome molybdenum alloy steel for high torque and durability.



CBBS12-S3



CBBS12-S3T

Part #	Product Description	
	AUTOMOTIVE/LIGHT TRUCK/TRAILER THIN WALL IMPACT SOCKETS	1/2" DRIVE
CBBS12-S3	3 Piece Set - 1/2" Drive - 17mm, 19mm, 21mm	✓
CBBS12-S3T	3 Piece Set - 1/2" Drive - 22mm, 7/8", 15/16"	✓

UNIVERSAL SOCKET



For lighter
duty jobs



Save time. For lighter-duty jobs.

Versatile

Comes with a 1/2" or 3/8" adapter attachment for power drills and ratchet wrenches. Instantly adjusts to grip hex nuts, hooks, eye and lag screws, bolt heads, and other various shape and size objects.

Durable Steel

Made with durable high carbon steel. 54 strong steel rods can automatically adjust to any size or shape.

One Size Fits Most

Suitable for standard screws, nuts, and bolts:

- 7/16" - 1-1/4" (11mm - 32mm)
- 3/8" - 1-1/16" (9mm - 27mm)
- 11/32" - 13/16" (9mm - 21mm)
- 1/4" - 3/4" (7mm - 19mm)



US12-1132



US12-927



US38-921



US38-719

Part #	Product Description*	1/2" Adapter	3/8" Adapter
US12-1132	Fits standard size 7/16" - 1-1/4" (11mm - 32mm) - Includes 1/2" adapter	✓	
US12-927	Fits standard size 1/2" - 1-1/16" (9mm - 27mm) - Includes 1/2" adapter	✓	
US38-921	Fits standard size 3/8" - 13/16" (9mm - 21mm) - Includes 3/8" adapter		✓
US38-719	Fits standard size 1/4" - 3/4" (7mm - 19mm) - Includes 3/8" adapter		✓

*Socket is not impact rated.

MAINTENANCE ACCESSORIES

**CBB-EP8****CBB-EP8 KIT****CBB-EP2****ECO-EP8****ECO-EP8 KIT**
CBB-LUBE8B
CBB-LUBE25B
CBB-LUBE40B
**CBB-EPB****ECO-EPB**

Part #	Product Description
CBB-EP8	CBB Euro-paste tire mounting compound - 7.7lbs
CBB-EP8 KIT	2 CBB Euro-paste buckets, 1 CBB Euro-paste brush
ECO-EP8 KIT	2 ECO Euro-paste buckets, 1 ECO Euro-paste brush
CBB-EP2	CBB Euro-paste motorcycle tire mounting compound - 2.2lbs
ECO-EP8	Eco-friendly ECO Euro-paste tire mounting compound - 7.7lbs
CBB-EPB	Counteract angled tire lubricant application brush
ECO-EPB	ECO tire lubricant application brush
CBB-LUBE8B	Premium tire mounting lube with rust inhibitors - 8lbs
CBB-LUBE25B	Premium tire mounting lube with rust inhibitors - 25lbs
CBB-LUBE40B	Premium tire mounting lube with rust inhibitors - 40lbs

LIQUID LUBE

16 fl. oz./473 ml Spray Bottle

High Performance Tire Mounting Lube for All Tire Types

- ✓ Ready to use
- 🔍 Dries fast, leaves no residue
- 🌀 Spray-on application
- 🌀 Prevents rim slippage



Part #	Product Description	Case Quantity
CBB-LL16	High performance sprayable tire mounting lube for all tire types - 16 fl. oz./473 ml	12

INSTRUCTIONS

Demounting: Apply after breaking the tire bead, spray liberally before demounting the tire. Helps prevent tire bead damage and reduces mounting head friction.

Mounting: Spray on tire bead areas to help seat the tire bead. Liquid Lube also tacks the tire to the rim, helping to prevent slippage.



MAINTENANCE ACCESSORIES

EV Counteract® LUBE

3.6 kg / 8 lbs

TIRE LUBE

Specially formulated
for high torque
electric vehicle
applications



**Protects
against rust**



**Synthetic based,
non-petroleum**



**Provides extreme tack
and adhesion minimizing
tire and rim slippage**



- Helps extend tire life on electric vehicles
- Quick mounting and demounting
- Protects tire bead and rim from damage during tire mounting

Part #	Product Description	Case Quantity
CBB-EV8	Electric Vehicle Tire Lube - 8lbs (3.6 kg)	4

Instructions

1. Thoroughly clean the surface of the wheel, rim and tire bead.
2. With a brush, apply the EV lubricant to the tire bead and the wheel/rim flange where the tire seats.
3. Inflate the tire and allow the tire bead to seat properly.
4. Reinstall the valve core and inflate the tire to the proper PSI stated by the vehicle manufacturer.



5th Wheel Grease

Available in 2oz Packets or 8oz Tubes

When you connect a traditional trailer or a 5th wheel to a commercial truck, it's important to lubricate the parts where they join together. This helps reduce friction and resistance between the metal surfaces.



MAINTENANCE ACCESSORIES

2oz Grease Packets

The Counteract 2oz packets are a game-changer for fleets, shops, and owner-operators. Each packet is filled with our premium grease allowing for an easy, mess-free application.



CBB-5WG2oz

8oz Grease Tubes

The 8oz squeeze tube is perfect for multiple applications. It can be used to not only lubricate the 5th wheel on commercial trucks and vehicles but can also be used to lubricate your standard trailer attachment for effortless towing.



CBB-5WG8oz

Part #	Product Description	Case Quantity
CBB-5WG2oz	5th Wheel Grease 2oz Packets	48
CBB-5WG8oz	5th Wheel Grease 8oz Tubes	12

Features

- Lasts twice as long as competing grease products
- Water-resistant
- Contains rust and corrosion inhibitors
- Two, easy to use applications
- Eliminates friction and premature wear on trailer attachments
- Our formula helps eliminate greasy messes on chassis and air hoses
- Minimizes steer tire wear
- Minimize premature wear on front end vehicle components
- Verified for use in all 4 seasons

Installation Instructions

TRADITIONAL TRAILER



COMMERCIAL TRUCK



WHEEL ACCESSORIES


Wheel Totes
& Felt Covers

Scan to learn
more & watch
the installation
video.



PREMIUM WHEEL TOTES

This tire carrying and storage system alleviates the mess and strain of seasonal tire change-over by covering your tires to protect your clothing and car interior from grime. These rugged 600D Oxford Fabric bags have built-in handles making them easy to carry and stack in the garage for storage. Each bag also presents a window card slot and wheel position identification image.

**EFFORTLESS LIFTING**

Handle makes it easy
to lift and carry tires

**STRONG & DURABLE**


Resistant to dirt,
water and UV rays

**WHEEL ICON MARKER**

Effortlessly mark the correct tire
and ensure proper placement

Part #	Product Description
CBB-WTM	Premium Wheel Totes 4 Pack (12" to 20")
CBB-WT	Premium Wheel Totes 4 Pack (20" to 31")

WHEEL FELT COVERS

**SECURE CLIPS**

Clips securely attach
to the wheel totes,
ensuring a seamless
hold every time



Compatible with
Counteract Wheel Totes

Part #	Product Description
CBB-WTFC	Wheel Felt Covers 4 Pack

Tire Mark-All

Counteract's Tire Mark-All Crayons offer tire professionals a reliable and durable solution for all tire marking needs.



TC12



TC20



TC50



Part #	Product Description	Case Quantity
TC12	Tire Mark-All Crayons - 12 Pack	50
TC20	Tire Mark-All Crayons - 20 Pack	50
TC50	Tire Mark-All Crayons - 50 Pack	20



Don't compromise on precision and visibility – choose Counteract Tire Mark-All for peace of mind in every tire-related task at your tire shop.

EFFORTLESS TIRE MARKING

Glide smoothly across challenging, rough or dirty surfaces leaving behind bold and clear markings. Ideal for all seasonal tire change, retread and tire repair marking needs.

VERSATILITY IN DIFFERENT CONDITIONS

No matter the weather or surface conditions, our crayons mark with ease on wet or cold rubber, ensuring consistent performance in various work environments.

EXTREME TEMPERATURE CONFIDENCE

Mark confidently in extreme temperatures, with a marking range from -50°F to 150°F (-45°C to 65°C), providing reliable performance even in the harshest winter chills or scorching summer heat.

WHEEL ACCESSORIES



WCS-B



WCS-C



WCS-D



WCS-B20




WCS-C20




WCS-D20



WCS-IT



3 PIECE INSTALL

5 PIECE INSTALL
(HEAVY DUTY)

Works in conjunction with your OEM style two-piece flange nuts. Designed to take-up the gap between the 22mm stud and 26mm wheel opening, re-aligning the wheel to the TRUE CENTER of the hub bearing. Increases fuel mileage and tire life, while reducing tire vibration and maintenance costs.

Part #	Product Description	MOQ
WCS-B	6 Piece Centering Sleeve Retail Pack - 22mm	10
WCS-C	100 Piece Centering Sleeve Bucket - 22mm	1
WCS-D	1,000 Piece Centering Sleeve Bucket - 22mm	1
WCS-B20	6 Piece Centering Sleeve Retail Pack - 20mm	10
WCS-C20	100 Piece Centering Sleeve Bucket - 20mm	1
WCS-D20	1,000 Piece Centering Sleeve Bucket - 20mm	1
WCS-IT	Centering Sleeve Installation Tool - 22mm, 20mm	1

**T12C****T13C****T13C-TPMS****T14C****T15C****T16C****T572C****T600C****T600C-C****T801C**

Part #	Product Description	MOQ
T12C	TR412 Tire Valve 33mm EPDM Rubber 100 Pack	1
T13C	TR413 Snap-in Tire Valve, for rim holes 11.5 (0.453 diameter), 1.25" tall, EPDM rubber 100 Pack	1
T13C-TPMS	TPMS Snap-in Tire Valve, for rim holes 11.5 (0.453 diameter), 2.25" tall, EPDM Rubber 100 Pack	1
T14C	TR414 Snap-in Tire Valve, for rim holes 11.5 (0.453 diameter), 1.50" tall, EPDM Rubber 100 Pack	1
T15C	TR415 Tire Valve 42.5mm EPDM Rubber 100 Pack	1
T16C	TR416 Tire Valve 40mm Brass - Nickel Plated 100 Pack	1
T572C	TR572 Tire Valve 100mm Brass 50 Pack	1
T600C	TR600 Tire Valve 42.5mm EPDM Rubber 100 Pack	1
T600C-C	TR600 Chrome Tire Valve 42.5mm EPDM Rubber - Chrome Plated 100 Pack	1
T801C	TR801 Tire Valve 50mm EPDM Rubber 100 Pack	1

WHEEL ACCESSORIES



VCB-FT



VCP-MK


VCC
VCP


VCR-MK



VCR2in1


VCCB-R
VCP-R

VCCB-G
VCP-G

VCCB-BK
VCP-BK

VCCB-B
VCP-B


VCC-ECO

Part #	Product Description
VCB-FT	Counteract Flowthrough Cap
VCP-MK	Counteract Motorcycle Logo Cap
VCC	Counteract Logo Cap - Copper
VCP	Counteract Logo Cap - Chrome Plated Plastic
VCR-MK	Motorcycle Valve Cap/Valve Core Remover Combo
VCR2in1	2-in-1 Valve Core Remover/Tire Valve Bleeder
VCCB-R	Red Cap - Copper
VCP-R	Red Cap - Chrome Plated Plastic
VCCB-G	Green Cap - Copper
VCP-G	Green Cap - Chrome Plated Plastic
VCCB-BK	Black Cap - Copper
VCP-BK	Black Cap - Chrome Plated Plastic
VCCB-B	Blue Cap - Copper
VCP-B	Blue Cap - Chrome Plated Plastic
VCC-ECO	ECO Balance Cap - Copper

WHEEL ACCESSORIES



Low Speed Driver



CBB-LSAD



CNT-107WB



CNT-22WB



CNT-22



CNT-28WB



CNT-33WB

Part #	Product Description
CBB-LSAD	Low Speed Air Driver. 52ft-lb tq, 1800 RPM, Non-Impact, Fwd/Rev Control
CNT-22	Nut Track holds up to ten 33mm Commercial Wheel Nuts for thread cleaning. Mountable to service station, truck, or bench. Includes 2 x CNT-22WB
CNT-107WB	10.7mm Wire Brush for cleaning valve stem mounting holes
CNT-22WB	22mm Wire Brush for cleaning inner threads on a 33mm nut
CNT-28WB	28mm Wire Brush for cleaning stud holes on hub piloted rims
CNT-33WB	33mm Wire Brush for cleaning wheel vents

WHEEL PRO

Page 14

Commercial Stud & Hub Cleaner



EASY SNAP-TECH DESIGN

Unlike competitors, Counteract's Wheel Pro & Wheel Pro XL feature a Snap-Tech design with interchangeable heads for fast brush changes. The vented tool body prevents tool lock by allowing rust and debris to dissipate during cleaning.

WHEEL ACCESSORIES



VCRT



VCV




VCV-ECO



VCR



WWR



TPG22



VP

Part #	Product Description
VCRT	Torquing Valve Core Tool
VCV	Counteract Vortex Valve Core
VCV-ECO	ECO Vortex Valve Core
VCR	Valve Core Tool/Flat Head Combo
WWR	Stick-on Wheel Weight Remover
TPG22	22mm Stud Thread Pitch Gauge
VP	Valve Stem Puller with Rubber Boot



CBB-IP



MK-RK



CBB-MKPG



SG-CBB

Part #	Product Description
CBB-IP	Injection Pump for Counteract Balancing Beads. Inject beads through valve stem. Hooks directly onto air line.
MK-RK	Motorcycle Tire Emergency Repair Kit
CBB-MKPG	Motorcycle 90 degree Tire Pressure Gauge
SG-CBB	Safety Glasses

WHEEL ACCESSORIES

Zafety Lug Lock®

**Prevent wheel loss by securing
your lug nuts to each other**

Designed, engineered and
manufactured in Canada

Zafety Lug Lock® creates resistance between two nuts minimizing their ability to rotate
The potential for wheel loss continues to be a significant safety concern for the transportation industry

Details

- Fast and easy to install/remove – flexible, simply fits over two adjacent nuts
- Lug nuts can be re-torqued without removing the Zafety Lug Lock®
- Laboratory tested in severe ambient temperature & vibration conditions
- Field tested at high and low rotation speeds on all types of surfaces
- 2-year Limited Manufacturers Defect Warranty
- Available in orange, red, white, blue, black, green, yellow, grey and custom colours


Design engineered high temperature plastic units formulated to withstand extreme changes in temperature – capable of withstanding continuous operating temperatures from -40°C (-40°F) to +160°C (+320°F) with transient temperature spikes up to +232°C (+450°F) - (important for vehicles that brake frequently e.g. city transit buses, waste collection trucks etc. and in certain geographic areas)

Benefits

- Provides a clear visual check in all weather and light conditions
- Reduces the risk of potential wheel loss (Protecting the public and avoiding owner or third party personal, vehicle, property & load damage, lost time & costly towing, road call fees & wheel repairs)
- Inexpensive, reusable and recyclable



How To Measure



WHEEL ACCESSORIES

Product Image	Part #	# Of Studs	Spacing		Nut Size		Application NA - North America, AU/NZ - Australia/New Zealand, UK/EU - United Kingdom/Europe
			Metric (Mm)	Us (Inches)	Metric (Mm)	Us (Inches)	
Delivery Type Vehicles							
	CBB-ZD41-X	6 & 8	111.1	4-3/8	41	1-39/64	Fuso (Mitsubishi), Hino, Ud (Nissan(Light Trucks (Varying Nut Sizes)
	CBB-ZD38-X	6	111.1	4-3/8	38.1	1-1/2	Curbside Delivery vehicles
Transit Bus & Coach Type Vehicles - includes some commercial truck vehicles							
	CBB-ZT33-X	10	104.8	4-1/8	33	1-5/16	NA - Public Transportation, Off-Road Vehicles, Coaches, UK/EU - Tractor Trailers AU/NZ - Residential Garbage Trucks, ISUZU, HINO
	CBB-ZT32-X	10	104.8	4-1/8	32	1-5/16	NA – Public Transportation (hybrids) UK/EU - Public Transportation & Tractor Trailers AU/NZ - Public Transportation
	CBB-ZT30-X	8	104.8	4-1/8	30	1-3/16	UK/EU - Lift axle on Tractor Trailers
	CBB-ZT27-X	6	104.8	4-1/8	27	1-1/16	UK/EU – Optare Buses, DAF
	CBB-ZT19-X	6	104.8	4-1/8	19	3/4	Mercedes Van
Commercial Trucking Type Vehicles - includes some bus & coach vehicles							
	CBB-ZC38-X	10	88.9	3-1/2	38.1	1-1/2	Some Prevost & MCI Coaches
	CBB-ZC33-X	10	88.9	3-1/2	33	1-5/16	NA - Large Trucks & Trailers, Ford, Mack, Freightliner, Kenworth, Western Star, etc., Type C & D School Buses, Utility Trucks, Ready Mix Trucks, AU/NZ - Large Trucks etc.
	CBB-ZC32-X	10	88.9	3-1/2	32	1-9/32	NA - some Large Trucks & Trailers UK/EU - Commercial Vehicles – Large Trucks & Trailers, AU/NZ - IVECO
Low Loader Type Vehicles							
	CBB-ZL33-X	8 & 10	69.9	2-3/4	33	1-5/16	NA - Low Loader Flatbed Trailers, Low Loader Semi-trailer, UK/EU - Low Profile Trailers, AU/NZ - Low Loader Flatbed Trailers
	CBB-ZL32-X	8 & 10	69.9	2-3/4	32	1-9/32	NA, UK, AU/NZ - Low Loader Vehicles
Van Type Vehicles							
	CBB-ZV21-X	6 & 8	69.9	2-3/4	21	13/16	F59 Chassis - Delivery Vans, Step Vans, Toyota 6-stud Vehicles, Ford Pickup Trucks
	CBB-ZV19-X	6	69.9	2-3/4	19	3/4	Ford Ranger, Mazda BT50 & ISUZU DMAX
	CBB-ZV25-X	6 & 8	63.5	2-1/2	25.4	1	Delivery Vans, Utility & Landscaping Trucks, Step Vans
	CBB-ZV21-X	6 & 8	63.5	2-1/2	22.2	7/8	Small Transit Buses, Delivery & Step Vans, Smaller Type A & B School Buses, EMS Vehicles, Ford 350, 450 & 550, Chevrolet Savana etc.
X - colour code • O-Orange • R-Red • W-White • G-Green • Y-Yellow • U-Blue • B-Black • E-Grey • D-Dark Grey • K-Dark Green							


X - colour code • O-Orange • R-Red • W-White • G-Green • Y-Yellow • U-Blue • B-Black • E-Grey • D-Dark Grey • K-Dark Green

Custom colours available.


WHEEL ACCESSORIES

COUNTERACT TRAPEZIUM STEEL ADHESIVE WHEEL WEIGHTS


Trapezium-shaped wheel weights offer superior wheel balancing by conforming perfectly to the wheel's curvature. This precise fit enhances weight distribution, reduces aerodynamic drag, and minimizes vibration, ensuring a smoother and more efficient ride. Ideal for high-performance and everyday vehicles, these weights exemplify precision engineering and quality.




SAWT-14R



SAWT-B14R



SAWT-12R




SAWT-B12R

Part #	Weight	Product Description
SAWT-14R	1/4oz	Reel of 1/4oz (0.25oz) trapezium steel adhesive wheel weights. Includes a total of 175oz or 700 individual weights. Zinc. Powder Coat.
SAWT-B14R	1/4oz	Reel of 1/4oz (0.25oz) black trapezium steel adhesive wheel weights. Includes a total of 175oz or 700 individual weights. Black Powder Coat.
SAWT-12R	1/2oz	Reel of 1/2oz (0.5oz) trapezium steel adhesive wheel weights. Includes a total of 150oz or 300 individual weights.
SAWT-B12R	1/2oz	Reel of 1/2oz (0.5oz) black trapezium steel adhesive wheel weights. Includes a total of 150oz or 300 individual weights. Black Powder Coat.

COUNTERACT STEEL ADHESIVE WHEEL WEIGHTS

Steel wheel weights offer numerous benefits, including being environmentally friendly due to their recyclability. They are durable, resisting corrosion and wear, which ensures long-lasting performance. Additionally, steel weights are cost-effective, providing a reliable and affordable solution for maintaining vehicle balance and safety.



SAWW-12R



SAWW-B12R



SAWW-P12



SAWW-B12

Part #	Weight	Product Description
SAWW-12R	1/4oz	Reel of 1/4oz (0.25oz) adhesive wheel weights. Includes a total of 176oz or 704 individual weights. Steel and Zinc.
SAWW-B12R	1/4oz	Reel of 1/4oz (0.25oz) black adhesive wheel weights. Includes a total of 176oz or 704 individual weights. Steel and Zinc. Black Powder Coat
SAWW-P12	1/2oz	Reel of 1/2oz (0.5oz) adhesive wheel weights. Includes a total of 178oz or 356 individual weights. Zinc. Powder Coat.
SAWW-B12	1/2oz	Reel of 1/2oz (0.5oz) black adhesive wheel weights. Includes a total of 178oz or 356 individual weights. Steel and Zinc. Black Powder Coat.

APPLICATION CHARTS

LIGHT TRUCK

	TIRE SIZE	1/2 TON	1 TON+		TIRE SIZE	1/2 TON	1 TON+		TIRE SIZE	1/2 TON	1 TON+
14"	215/75R14	3	4		195/65R16	3	4		225/80R17.5	8	8
	205/70R14	3	4		215/65R16	3	4		205/75R17.5	6	6
	215/70R14	3	4		225/65R16	3	4		215/75R17.5	6	6
15"	700R15		4		245/65R16	3	4		225/75R17.5	6	6
	7.50R15		6		255/65R16	3	4		235/75R17.5	6	6
	8.25R15		6		305/65R16	3	4		245/75R17.5	6	6
	9R15		8		345/65R16	5	6		195/70R17.5	6	6
	10R15		8		375/65R16	5	6		215/70R17.5	6	6
	215/80R15	3	4		215/60R16	3	4		235/70R17.5	6	6
	195/75R15	3	4		225/60R16	3	4		195/60R17.5	6	6
	205/75R15	3	4		235/60R16	3	4		205/60R17.5	6	6
	225/75R15	4	4		285/60R16	3	4		225/60R17.5	6	6
	235/75R15	4	4		255/55R16	3	4	18"	7.50R18	8	8
	245/75R15	3	4		315/55R16	3	4		255/70R18	3	5
	255/75R15	3	4		345/55R16	3	5		265/70R18	3	5
	265/75R15	3	4		355/55R16	3	5		275/70R18	4	6
	235/70R15	3	4		375/55R16	4	6		275/65R18	4	6
	245/70R15	3	4		245/50R16	3	4		285/65R18	4	6
	255/70R15	3	4		8R16.5	5	5		325/65R18	4	6
	265/70R15	4	4		9.50R16.5	6	6		355/65R18	4	6
	285/70R15	4	4		10R16.5	6	6		395/65R18	6	8
	315/70R15	4	5		12R16.5	8	8		245/60R18	3	4
	245/65R15	3	4		235/80R17	6	6		255/60R18	3	5
	225/60R15	3	4		235/75R17	6	6		265/60R18	3	5
	325/60R15	4	5		245/75R17	6	6		275/60R18	4	6
	185/70RW15.5	3	4		255/75R17	6	6		285/60R18	4	6
	6.50R16		4		285/75R17	6	6		325/60R18	4	6
15.5"	7.50R16		4	16"	245/70R17	4	6		375/60R18	6	8
	8.25R16		6		255/70R17	4	6		395/60R18	6	8
	11R16		8		265/70R17	6	6		255/55R18	3	4
16"	215/85R16	3	4		275/70R17	6	6	19"	275/55R18	3	4
	225/85R16	3	4		285/70R17	6	6		285/55R18	3	4
	235/85R16	3	4		305/70R17	6	8		285/50R18	3	4
	245/85R16	3	4		315/70R17	6	8		375/50R18	4	6
	255/85R16	4	5		355/70R17	6	8		255/55R19	3	4
	265/85R16	4	5		225/65R17	3	4		255/50R19	3	4
	275/85R16	4	5		235/65R17	3	4		275/45R19	3	4
	205/80R16	3	4		245/65R17	3	4		285/45R19	3	4
	325/80R16	4	6		255/65R17	3	5		325/75R20	6	8
	175/75R16	3	4		265/65R17	4	6	20"	275/65R20	4	6
	195/75R16	3	4		305/65R17	4	6		275/60R20	4	6
	225/75R16	3	4		375/65R17	6	8		325/60R20	4	6
	235/75R16	3	4		225/60R17	3	4		355/60R20	5	6
	245/75R16	3	4		235/60R17	3	4		275/55R20	3	4
	265/75R16	4	6		255/60R17	4	6		285/55R20	3	4
	285/75R16	4	6		275/60R17	4	6		255/50R20	3	4
	295/75R16	4	6		285/60R17	4	6		285/50R20	3	4
	315/75R16	4	6		225/60R17	3	4		305/50R20	4	6
	215/70R16	3	4		255/55R17	3	4		325/50R20	4	6
	225/70R16	3	4		275/55R17	3	5		355/50R20	4	6
	235/70R16	3	4		345/55R17	3	5		325/45R20	4	6
	245/70R16	3	4		255/50R17	3	4		275/40R20	4	6
	255/70R16	3	4		8R17.5	5	5	22"	315/35R20	4	6
	265/70R16	3	4		8.5R17.5	6	6		325/55R22	5	6
	275/70R16	3	4		9R17.5	6	6		335/55R22	5	6
	305/70R16	3	4		9.5R17.5	8	8		325/50R22	4	6
	315/70R16	4	6		10R17.5	8	8		305/45R22	4	6
	355/70R16	5	6		11R17.5	8	8		305/40R22	4	6
	365/70R16	5	6		225/90R17.5	8	8		285/35R22	3	5
	395/70R16	5	6		205/80R17.5	8	8		325/45R24	4	6

To achieve maximum results, it is important to use the proper package size for each tire. The amount of Counteract required per tire is based on one ounce per thirteen pounds of tire and rim combination. If you are using our throw in bags, open and discard outside bag only, and throw clear inner bag directly into the tire. It is imperative that none of the contents of the bag end up on the bead seating area of the tire and rim. In order to reduce the possibility of valve leaks, the use of Counteract's Vortex Valve Core, and Counteract Valve Cap is recommended. The core and cap are included in every bag of Counteract. Counteract is TPMS safe and compatible. Always wear safety glasses when installing CBB. Counteract disclaims any responsibility for air loss or tire damage due to improper installation or air check.


APPLICATION CHARTS



3	3oz	10	10oz
4	4oz	12	12oz
5	5oz	14	14oz
6	6oz	16	16oz
8	8oz	20	20oz

How much Counteract for your tire?

MED-HEAVY DUTY TRUCK							
	TIRE SIZE	SINGLE	DUALY		TIRE SIZE	SINGLE	DUALY
19.5"	8R19.5	10	10	24"	385/65R22.5	14	16
	9R19.5	10	10		425/65R22.5	16	16
	18R19.5	16	16		445/65R22.5	20	
	280/75R19.5	12	12		285/60R22.5	12	14
	285/75R19.5	12	12		295/60R22.5	12	14
	225/70R19.5	10	10		305/60R22.5	12	14
	245/70R19.5	10	10		315/60R22.5	12	14
	265/70R19.5	12	12		385/55R22.5	12	
	275/70R19.5	12	12		455/55R22.5	16	
	285/70R19.5	12	12		275/50R22.5	10	12
	305/70R19.5	14	14		445/50R22.5	20	
	385/65R19.5	14	14		11.00R24	14	
	445/65R19.5	16	16		12.00R24	14	
					14.00R24	16	
20"	7.50R20	8	10	24.5"	445/70R24	16	
	8.25R20	8	10		495/70R24	16	
	9.00R20	10	12		11R24.5	12	14
	10.00R20	10	12		12R24.5	16	16
	11.00R20	12	14		285/75R24.5	12	14
	12.00R20	12	14		305/75R24.5	12	14
	12.5R20	12	14		315/75R24.5	12	14
	13/80R20	12	14		275/80R24.5	12	14
	13/80R20	12	14		295/80R24.5	12	14
	14.00/R20	16	16				
	365/80R20	16	16				
	395/80R20	16	16				
20.5"	525/65R20.5	20					
	615/65R20.5	20					
22"	10.00R22	12					
	11.00R22	12					
22.5"	9R22.5	10	12				
	10R22.5	10	12				
	11R22.5	12	14				
	12R22.5	12	14				
	13R22.5	12					
	15R22.5	16					
	16R22.5	16					
	16.5R22.5	16					
	18R22.5	20					
	235/80R22.5	8	10				
	255/80R22.5	10	12				
	275/80R22.5	12	14				
	295/80R22.5	14	16				
	315/80R22.5	16					
	365/80R22.5	16					
	245/75R22.5	10	12				
	265/75R22.5	12	14				
	285/75R22.5	12	14				
	295/75R22.5	12	14				
	315/75R22.5	14	16				
	345/75R22.5	14	16				
	350/75R22.5	14	16				
	235/70R22.5	8	10				
	255/70R22.5	10	12				
	11/70R22.5	10	12				
	265/70R22.5	10	12				
	275/70R22.5	10	12				
	305/70R22.5	10	12				
	315/70R22.5	10	12				
	365/70R22.5	14	16				
	365/65R22.5	14	16				



Scan to
download
our app
for quick
calculations!

For more information
about our app and
rewards program
check out

Pages 4 & 5



APPLICATION CHARTS

15"	TIRE SIZE			A/T	M/T		TIRE SIZE			A/T	M/T		TIRE SIZE			A/T	M/T
	14/17R15	12	14	16"	39.5/13.5R15	12	14	16.5"	44/19.5R16	14	16	18"	39.5/13.5R17	12	14		
	26/16.5R15	12	14		39.5/15R15	12	14		44/21R16	14	20		39.5/15R17	12	14		
	27/9.5R15	6	6		39.5/18R15	12	14		46/19.5R16	14	20		40/13.5R17	14	16		
	29/10.5R15	6	6		40/16R15	12	14		325/80R16.5	8	10		41/14.5R17	14	16		
	29/11.5R15	6	6		40/17R15	12	14		31/10.5R16.5	6	8		42/14R17	14	16		
	29/8.5R15	6	6		42/14R15	12	14		33/11.5R16.5	8	10		42/15R17	14	16		
	29/9.5R15	6	6		42/15R15	12	14		33/12.5R16.5	10	12		44/21R17	16	20		
	30/10.5R15	6	6		44/18.5R15	14	16		33/14.5R16.5	10	12		49/21R17	16	20		
	30/11.5R15	6	8		44/19.5R15	14	16		33/14R16.5	10	12		33/12.5R18	10	12		
	30/9.5R15	6	8		44/21R15	14	16		33/15.5R16.5	10	12		33/13.5R18	10	12		
	31/10.5R15	6	8		46/19.5R15	14	16		33/16.5R16.5	10	12		34/12.5R18	10	12		
	31/11.5R15	8	10		Q78	12	14		34/9.5R16.5	8	10		35/12.5R18	12	14		
	31/11R15	8	10		255/85R16	8	10		35/12.5R16.5	12	14		35/14.5R18	10	12		
	31/12.5R15	6	8		30/11.5R16	6	8		35/14.5R16.5	10	12		36/12.5R18	10	12		
	31/13.5R15	8	8		31/11.5R16	8	10		35/15.5R16.5	10	12		37/12.5R18	12	14		
	31/14.5R15	8	10		31/11R16	8	10		35/15R16.5	12	14		37/13.5R18	12	14		
31/9.5R15	6	8	31/12.5R16	8	10	35/16R16.5	10	12	38/14.5R18	12	14						
32/10.5R15	8	10	32/10R16	8	10	36/12.5R16.5	10	12	38/15.5R18	12	14						
32/11.5R15	8	10	32/11.5R16	8	10	36/13.5R16.5	10	12	38.5/14.5R18	12	14						
32/12.5R15	8	10	32/12.5R16	8	10	36/14.5R16.5	12	14	40/14.5R18	14	16						
32/9.5R15	8	10	32/9.5R16	8	10	36/16.5R16.5	12	14	41/14.5R18	14	16						
33/10.5R15	8	10	32/9R16	8	10	37/12.5R16.5	12	14	33/12.5R20	10	12						
33/11.5R15	8	10	33/10.5R16	8	10	37/13R16.5	10	12	34/10.5R20	10	12						
33/12.5R15	8	10	33/11.5R16	8	10	37/14R16.5	12	14	35/12.5R20	12	14						
33/13.5R15	8	10	33/12.5R16	8	10	38/12.5R16.5	10	12	35/14.5R20	12	14						
33/14.5R15	10	12	33/12R16	8	10	38/15.5R16.5	12	14	36/13.5R20	12	14						
33/14R15	10	12	33/13.5R16	8	10	38.5/11R16.5	10	12	37/12.5R20	12	14						
33/15.5R15	10	12	33/13R16	8	10	38.5/14.5R16.5	12	14	37/13.5R20	12	14						
33/16.5R15	10	12	33/14.5R16	10	12	38.5/15R16.5	12	14	38/13.5R20	12	14						
33/9.5R15	8	10	33/14R16	10	12	38.5/16R16.5	12	14	38/15.5R20	12	14						
34/12.5R15	8	10	34/10.5R16	8	10	39.5/13.5R16.5	12	14	38.5/14.5R20	12	14						
34/9.5R15	8	10	34/12.5R16	10	12	39.5/15R16.5	12	14	39.5/13.5R20	12	14						
35/10.5R15	8	10	34/9R16	6	8	39.5/18R16.5	14	16	39.5/15R20	12	14						
35/12.5R15	8	10	35/10.5R16	8	10	40/15.5R16.5	14	16	40/14.5R20	14	16						
35/13.5R15	10	12	35/12.5R16	12	14	40/17R16.5	14	16	40/15.5R20	14	16						
35/14.5R15	10	12	35/14.5R16	12	14	42/14R16.5	14	16	41/14.5R20	14	16						
35/15.5R15	10	12	35/16R16	12	14	42/14R16.5	14	16	42/14R20	14	16						
35/15R15	10	12	36/12.5R16	12	14	42/15R16.5	14	16	42/15R20	14	16						
35/16R15	10	12	36/13.5R16	12	14	44/18.5R16.5	16	20	44/21R20	16	20						
36/12.5R15	10	12	36/13R16	12	14	44/19.5R16.5	16	20	49/21R20	16	20						
36/13.5R15	10	12	36/14.5R16	12	14	44/21R16.5	14	20	33/12.5R22	10	12						
36/14.5R15	12	14	36/14R16	12	14	46/17R16.5	16	20	35/12.5R22	12	14						
36/15.5R15	12	14	37/12.5R16	12	14	46/19.5R16.5	16	20	35/14.5R22	14	16						
36/16.5R15	12	14	37/13R16	12	14	47/17R16.5	16	20	37/12.5R22	14	16						
37/12.5R15	10	12	37/14R16	12	14	47/19.5R16.5	16	20	37/13.5R22	14	16						
37/13R15	10	12	38/13R16	12	14	49/21R16.5	16	20	38/13.5R22	14	16						
37/14.5R15	12	14	38/14.5R16	12	14	33/12.5R17	10	12	38/15.5R22	14	16						
37/14R15	12	14	38/15.5R16	12	14	33/13.5R17	10	12	40/14.5R22	14	16						
38/12.5R15	10	12	38.5/11R16	10	12	34/10.5R17	12	14	40/15.5R22	14	16						
38/15.5R15	12	14	38.5/14.5R16	12	14	35/12.5R17	12	14	41/14.5R22	14	16						
38.5/11R15	10	12	38.5/15R16	12	14	35/14.5R17	12	14	35/13.5R24	14	16						
38.5/14.5R15	12	14	39.5/13.5R16	12	14	36/13.5R17	12	14	37/13.5R24	14	16						
38.5/15.5R15	12	14	39.5/15R16	12	14	37/12.5R17	12	14	38/13.5R24	14	16						
38.5/15R15	12	14	40/14.5R16	14	16	37/13.5R17	12	14	38/14R24	14	16						
38.5/16.5R15	12	14	41/14.5R16	14	16	37/13R17	12	14	40/14.5R24	14	16						
38.5/16R15	12	14	42/14R16	14	16	38/15.5R17	12	14	40/15.5R24	14	16						
39/15R15	12	14	42/15R16	14	16	38.5/14.5R17	12	14	40/15.5R26	14	16						

There are many variables that contribute to vibration in "mudder" tires. Before installing Counteract, please consider the following sources of vibration, including but not limited to: Proper drive line angle, tire pressure, presence of a lift kit, tire run-out, wheel run-out, extreme side wall flex, tread ripple, and/or a lug pattern that may cause acoustical vibration. These factors, and others, will play a role in the vibration of the vehicle and Counteract will not correct these conditions. We cannot guarantee the elimination of all vibration sources.

APPLICATION CHARTS

FRONT TIRE WIDTH	OUNCES REQUIRED
80mm-120mm	1
130mm-240mm	2
240mm - Up	3

REAR TIRE WIDTH	OUNCES REQUIRED
130mm-240mm	2
250mm-360mm	3
195-205 Car Tire on Rear	3

SCOOTERS	OUNCES REQUIRED
10" Rim Diameter	1
12" & Up Rim Diameter	2

DUAL PURPOSE, DIRT BIKE WITH RIM LOCK	OUNCES REQUIRED
Front 80mm-120mm	2
Rear 130mm-230mm	3

TUBE TYPE TIRE, WIRE SPOKE RIM	OUNCES REQUIRED
80mm-120mm	2
130mm-240mm	2

Harley-Dunlop Tire Size Conversion (MT90B16)

MT, MH, MJ etc. = Tire Width, 90 = Tire Profile, B = Rim Diameter

MH = 80mm Width	MR = 120mm Width
MJ = 90mm Width	MT = 130mm Width
MM = 100mm Width	MU = 140mm Width
MN or MP = 110mm Width	MV = 150mm Width

PLEASE NOTE EXCEPTIONS BELOW

- 1) Super Sport bikes can experience a vibration at high triple digit speeds because too much product was added.
Please start with 1/2oz in the front tire, regular recommended amount in the rear.

(ZX1000, CBR1000RR, CBR600RR, ZX600R, R1, R6, RC8, etc.)



EXAMPLE:

WIDTH / ASPECT RATIO x RIM DIAMETER

110/90x19

APPLICATION CHARTS

All ATV & UTV applications are based on the height of the tire.



Note: Due to the nature and uses of ATV/UTV tires, Counteract cannot guarantee a 100% balance. The use of this product in ATV/UTV applications is for a smoother, less fatiguing drive with an 80% decrease in vibration. Counteract is however the best means of providing balance to these applications.

TIRE HEIGHT	OUNCES REQUIRED
23" - 29"	4
30" - 33"	6
33" - 37"	8
37" - Up	10

Disclaimer

Counteract does not accept any responsibility for use in Sand Paddle tires. These tires are not designed to be driven on road, and therefore cannot be balanced.



APPLICATION CHARTS

	TIRE SIZE	OUNCES REQUIRED
12"	125R12	3
14"	P175/70R14	3
	P185/70R14	3
	P215/70R14	3
	P165/75R14	3
	P205/75R14	3
	F70/14	3
	G70/14	3
	695/14	4
	750/14	4
	800/14	4
15"	P205/75R15	3
	P215/75R15	3
	P225/75R15	4
	P235/75R15	4
	P215/70R15	4
	775/15	4
	E70/15	4
	F70/15	4
	F60/15	4
	G60/15	4
	670/15	4
	710/15	4
	760/15	4
	155 S R15	4
16"	600/16	4
	650/16	4
19"	450/19	4
	475/19	4
21"	4.40R21	4
	4.50R21	4
30"	30" X 3"	6
	30" X 3.5"	6



Modern reproduction wire wheels for Model T = 2oz

21" wire wheels (26/27 Model T) = 4oz

19" wheels (Model A, etc) = 4oz

17" wheels (30s cars) = 4oz

Vintage cars with wooden spokes and demountable rims = 6oz

Vintage cars with wooden spokes and felloes = Minimum of 5oz


Pre- WW1 Oldsmobile = Minimum 6oz

These weights are based on a guideline of 1oz of beads per 13lbs of wheel and tire weight.

Note: older wheels tend to be more out of balance.

APPLICATION CHARTS

WHEEL DIAMETER	TIRE SIZE	CBB REQUIRED
8"	4.80/4.00 R8	3
	5.70 R8	3
	165/65 R8	3
	215/60 R8	3
9"	6.90/6.00 R9	3
10"	205/65 R10	3
12"	4.80 R12	3
	5.30 R12	3
	145/80 R12	3
13"	175/80 R13	4
	185/80 R13	4
14"	205/75 R14	4
	215/75 R14	4
14.5"	9.00 R14.5	8
15"	205/75 R15	4
	215/75 R15	4
	225/75 R15	4
	7.00 R15	6
16"	215/85 R16	4
	235/80 R16	4
	235/85 R16	4
	7.50 R16	6
16.5"	12.00 R16.5	8
17.5"	215/75 R17.5	8
	235/75 R17.5	8
	245/70 R17.5	8
19.5"	225/70 R19.5	10
	245/70 R19.5	10
	265/70 R19.5	12
22.5"	255/70 R22.5	12
	295/75 R22.5	12
	11 R22.5	12



LOAD RANGE	PLY RATING
A	2
B	4
C	6
D	8
E	10
F	12
G	14
H	16
J	18
L	20
M	22
N	24

3	3oz	10	10oz
4	4oz	12	12oz
5	5oz	14	14oz
6	6oz	16	16oz
8	8oz	20	20oz


How much Counteract
for your tire?

Visit howmuchcounteract.com or
scan the QR code to download our app



APPLICATION CHARTS

WHEEL DIAMETER	TIRE SIZE	SINGLE	DUALY
8"	215/60 R8	3	
	165/65 R8	3	
	4.80/4.00 R8	3	
	5.70 R8	3	
9"	6.90/6.00 R9	3	
10"	205/65 R10	3	
12"	4.80 R12	3	
	5.30 R12	3	
	145/80 R12	3	
13"	175/80 R13	4	
	185/80 R13	4	
14"	205/75 R14	4	
	215/75 R14	4	
14.5"	9.00 R14.5	8	
15"	205/75 R15	4	
	215/75 R15	4	
	225/75 R15	4	
	7.00 R15	6	
16"	225/75 R16	4	4
	245/75 R16	4	4
	235/80 R16	4	
	215/85 R16	4	4
	235/85 R16	4	4
	7.50/7.5 R16	6	
16.5"	12.00 R16.5	8	8
17.5"	245/70 R17.5	8	8
	215/75 R17.5	8	8
	235/75 R17.5	8	8
	9.00 R17.5	6	6
19.5"	225/70 R19.5	10	
	245/70 R19.5	10	10
	265/70 R19.5	12	12
	285/70 R19.5	12	12
22.5"	10 R22.5	10	12
	11 R22.5	12	14
	12 R22.5	12	14
	255/70 R22.5	10	12
	275/70 R22.5	10	12
	305/70 R22.5	10	12
	365/70 R22.5	14	16
	295/75 R22.5	12	14
	235/80 R22.5	8	10
	255/80 R22.5	10	12
	275/80 R22.5	12	14
	295/80 R22.5	14	16
	315/80 R22.5	16	



3	3oz	10	10oz
4	4oz	12	12oz
5	5oz	14	14oz
6	6oz	16	16oz
8	8oz	20	20oz

How much Counteract for your tire?

Visit howmuchcounteract.com or scan the QR code to download our app



MARKETING



Product	Description/Part #			
Counteract Brochures	Balancing Beads Brochure - CBBA-CBB Motorcycle Beads Brochure - CBBA-MK Off Road Beads Brochure - CBBA-OR Centering Sleeves Brochure - CBBA-CS			
Tire Brochure Display Holder	CBBP-TD			
Counteract Application Charts	17x22 Application Chart - CBBA-ACW			
Shop Marketing Banner	Counteract Truck Banner - CBBP-BT Counteract Motorcycle Banner - CBBP-BM			
Counteract Counter Mat (12x18)	Truck Counter Mat - CBBP-CMT Motorcycle Counter Mat - CBBP-CMM			
Counteract Shaker Bottle	Shaker Bottle - CBBP-SB Shaker Bottle Lid - CBBP-SBL			
Beanies	Motorcycle Beanie - CBBP-BB Truck Beanie - CBBP-BG			
Bandanas	Black Motorcycle Bandana - CBBP-BMK Camo Motorcycle Bandana - CBBP-BCAMO			
Hats	Truck Hat - CBBP-HB Motorcycle Hat - CBBP-HG			
Counteract Golf Shirt	S - CBBP-GSS M - CBBP-GSM	L - CBBP-GSL XL - CBBP-GSXL	2XL - CBBP-GS2XL 3XL - CBBP-GS3XL	4XL - CBBP-GS4XL 5XL - CBBP-GS5XL
Counteract Motorcycle T-Shirt (Black)	S - CBBP-MSBS M - CBBP-MSBM	L - CBBP-MSBL XL - CBBP-MSBXL	2XL - CBBP-MSB2XL 3XL - CBBP-MSB3XL	
Counteract Motorcycle T-Shirt (Grey)	S - CBBP-MSGs M - CBBP-MSGM	L - CBBP-MSGl XL - CBBP-MSGXL	2XL - CBBP-MSG2XL 3XL - CBBP-MSG3XL	4XL - CBBP-MSG4XL 5XL - CBBP-MSG5XL
Red Pill Box Keychain	CBBP-RPKC			

All merchandise and marketing material is subject to availability.


LOOKING TO **CONNECT** WITH COUNTERACT?

Scan this QR code on your wireless device
to sign up for new product alerts emails,
and connect with us on Social Media.



Use #teamcounteract for a chance
to win our monthly giveaway!

www.teamcounteract.com





NORTH AMERICA

555 Southgate Drive
Guelph, ON N1G 3W6
Tel.: 1-519-837-3331
Toll Free: 1-800-572-8952
contact@counteractbalancing.com



EUROPE & AFRICA

R. Vieira 152, 3750-463
Fermentelos, Portugal
Tel.: (351) 234 941 294
info@cbbe.eu



BRAZIL & SOUTH AMERICA

Counteract, Balanceamento Automático Ltda
Rua Rio Para, 675, Unit 2, Sete lagos Mg, Brasil
Tel.: 55 -31-3773-0654
administrativo@counteract.com.br
www.counteract.com.br